

DYNAMICAL SYSTEMS AND TRAFFIC CONTROL

Invited Guest Lecture in 18.085/18.0851 Computational Science and Engineering I

Claudio Lombardi^{1,2,*}

¹CERIS, Instituto Superior Técnico, Universidade de Lisboa, Av. Rovisco Pais 1, 1049-001, Lisboa, Portugal

²Active Adaptive Control Laboratory, Department of Mechanical Engineering, MIT, Cambridge, MA, USA

Massachusetts Institute of Technology, 12th August 2020

DYNAMICAL SYSTEMS AND TRAFFIC CONTROL

Claudio Lombardi

Claudio Lombardi

- 2014** B.Sc. degree in Civil Engineering from Politecnico di Milano
- 2016** M.Sc. degree in Civil Engineering from Politecnico di Milano and IST
- 2016 - on going** Ph.D. in Transportation system at Instituto Superior Técnico (IST)

Oct 2018 – Jan 2019 visiting Ph.D. student at AAC Lab, MIT

Sept 2019 – Apr 2020 visiting Ph.D. student at AAC Lab, MIT

webpage: <https://fenix.tecnico.ulisboa.pt/homepage/ist422646>

linkedin: <https://www.linkedin.com/in/lombardiclaudio/>

Dynamical systems

First-order continuous-time homogeneous system of linear ordinary differential equations:

$$\dot{\mathbf{x}}(t) = \mathbf{A}(t) \cdot \mathbf{x}(t)$$

$$\dot{\mathbf{x}}(t) - \mathbf{A}(t) \cdot \mathbf{x}(t) = 0$$

If $\mathbf{A}(t) = \mathbf{A}$ (LTI system) and \mathbf{A} has n linearly independent eigenvectors, the system has the following general solution:

$$\mathbf{x}(t) = c_1 \cdot e^{\lambda_1 t} \cdot \mathbf{u}_1 + c_2 \cdot e^{\lambda_2 t} \cdot \mathbf{u}_2 + \dots + c_n \cdot e^{\lambda_n t} \cdot \mathbf{u}_n$$

$\lambda_1, \lambda_2, \dots, \lambda_n$ eigenvalues of \mathbf{A}


$\mathbf{u}_1, \mathbf{u}_2, \dots, \mathbf{u}_n$ eigenvectors of \mathbf{A}

c_1, c_2, \dots, c_n constants

DYNAMICAL SYSTEMS AND TRAFFIC CONTROL

Claudio Lombardi

Stability (one dimensional graph)



Asymptotically stable

**Asymptotically stable
(with oscillations)**

© Gianni A. Di Caro. All rights reserved. This content is excluded from our Creative Commons license. For more information, see <https://ocw.mit.edu/fairuse>.

Traffic Density

Usually indicated by Greek letter ρ .


It is the number of vehicles occupying a unit length of roadway.

$$\rho = \frac{q}{v}$$

ρ traffic density [n° of vehicles/km]

q traffic flow [n° of vehicles/h]

v traffic average speed [km/h]




DYNAMICAL SYSTEMS AND TRAFFIC CONTROL

Claudio Lombardi

Traffic control


(Phan et al., 2016):

$$(e(t) = 0, \dot{e}(t) = 0) \text{ equilibrium point}$$



© IEEE. All rights reserved. This content is excluded from our Creative Commons license. For more information, see <https://ocw.mit.edu/fairuse>.

$$u = K_p \cdot e + K_d \cdot \dot{e}$$



$$\dot{\rho}(t) = a \cdot \rho(t) + b \cdot \rho_{ref}(t)$$

© Gianni A. Di Caro. All rights reserved. This content is excluded from our Creative Commons license. For more information, see <https://ocw.mit.edu/fairuse>.

Traffic control

$$\dot{\rho}(t) = a \cdot \rho(t) + b \cdot \rho_{ref}(t)$$

$$\dot{\rho}(t) - a \cdot \rho(t) = b \cdot \rho_{ref}(t)$$

$$\dot{x}(t) - a \cdot x(t) = b \cdot u(t)$$

It is a first-order continuous-time forced linear ordinary differential equation.

In traffic engineering the forcing term is typically constant:

$$\rho_{ref}(t) = \rho_{ref}$$

Traffic control

$$\dot{x}(t) - a \cdot x(t) = b \cdot u(t)$$

The properties of the solution of the forced system are still dictated by the associated homogeneous system:

$$\dot{x}(t) - a \cdot x(t) = 0$$

The eigenvalue(s) of the system are related to the definition of parameters K_p and K_d . If K_p and K_d are chosen so that the eigenvalues of the system are in the portion of the complex plane with negative real part, asymptotic stability of the solution is guaranteed, meaning that, theoretically, density should tend to the desired value asymptotically.

$\dot{\rho}(t) = 0$ and $\rho(t) = \rho_{ref}$ is the equilibrium point of the system we are aiming at.

Traffic control – multiple control sections

If density is controlled only in one section of the facility, we have an ordinary differential equation:

$$\dot{\rho}(t) - a \cdot \rho(t) = b \cdot \rho_{ref}(t)$$

If density is controlled in multiple points of the facility, we have a system of ODEs:

$$\dot{\rho}(t) - \mathbf{A} \cdot \rho(t) = \mathbf{B} \cdot \rho_{ref}(t)$$

Previous considerations regarding stability are still valid.

Digital traffic control

Typically controllers are digital, meaning that they work in discrete-time. If density is controlled only in one section of the facility, we have a recursive equation:

$$\rho(k + 1) - a \cdot \rho(k) = b \cdot \rho_{ref}(k)$$

If density is controlled in multiple points of the facility, we have a system of recursive equations:

$$\boldsymbol{\rho}(k + 1) - \mathbf{A} \cdot \boldsymbol{\rho}(k) = \mathbf{B} \cdot \boldsymbol{\rho}_{ref}(k)$$

Digital traffic control

For the system

$$\mathbf{x}(k + 1) - \mathbf{A} \cdot \mathbf{x}(k) = 0$$

The solution is

$$\mathbf{x}(k) = c_1 \cdot \lambda_1^k \cdot \mathbf{u}_1 + c_2 \cdot \lambda_2^k \cdot \mathbf{u}_2 + \dots + c_n \cdot \lambda_n^k \cdot \mathbf{u}_n$$


$\lambda_1, \lambda_2, \dots, \lambda_n$ eigenvalues of \mathbf{A}

$\mathbf{u}_1, \mathbf{u}_2, \dots, \mathbf{u}_n$ eigenvectors of \mathbf{A}

c_1, c_2, \dots, c_n constants depending on the initial condition

Digital traffic control

There is stability for eigenvalues that are inside the unit circle around the origin of the complex plane.



Courtesy Elsevier, Inc., <http://www.sciencedirect.com>. Used with permission.

DYNAMICAL SYSTEMS AND TRAFFIC CONTROL

Claudio Lombardi

References

T. Phan, A. M. Annaswamy, D. Yanakiev, and E. Tseng, “A model-based dynamic toll pricing strategy for controlling highway traffic,” in Proc. Amer. Control Conf. (ACC), 2016, pp. 6245–6252.

M. Sami Fadali, and A. Visioli. Digital Control Engineering: Analysis and Design. 3rd ed. Academic Press, 2020.

MIT OpenCourseWare
<https://ocw.mit.edu>

18.085 Computational Science and Engineering I
Summer 2020

For information about citing these materials or our Terms of Use, visit: <https://ocw.mit.edu/terms>.