# On-line versus Off-line Learning in the Linear Perceptron: a Comparative Study

**Osame Kinouchi**[*] and **Nestor Caticha**[†]
Instituto de Física, Universidade de São Paulo
Caixa Postal 20516, 01452-990 São Paulo, SP, Brazil

**Abstract**

The spherical perceptron with $N$ inputs and a linear output does not present optimal generalization if trained by minimization of the standard quadratic cost function

$$\mathcal{E} = \frac{1}{2}\sum_{\mu=1}^{\alpha N}(b_\mu - h_\mu)^2,$$

where $b_\mu$ and $h_\mu$ are the outputs from the rule (teacher) and hypothesis (student) networks for the example $\mu$ and there are $\alpha N$ examples. We derive an optimal algorithm for *on-line* learning of examples which outperforms the exhaustive (*off-line*) standard algorithm for $\alpha$ up to 0.71. The on-line optimized algorithm suggests a class of cost functions for *off-line* learning, which we then proceed to study using the replica method. The optimized cost function within that class has the suggestive form

$$E = \alpha N\left[\Gamma\frac{1}{\alpha N}\sum_{\mu=1}^{\alpha N}(-\ln P(b_\mu \mid h_\mu)) - \Gamma \ln Z\right],$$

where $Z$ is a normalization constant, $P(b_\mu \mid h_\mu)$ is the conditional probability of the output data $b_\mu$ given the hypothesis output $h_\mu$ and $\Gamma$ is a learning parameter analogous to a temperature which decreases in a well defined manner along the learning process.

**Key words:** *neural networks, generalization, linear perceptron, learning algorithms, maximum likelihood, pseudoinverse, Adaline.*

PACS. #: 02.50, 05.90, 87.10.

[*]E-mail: osame@if.usp.br
[†]E-mail: nestor@if.usp.br

# 1 Introduction

The ability of generalization (rule extraction) is the simplest possible cognitive-like property, besides functioning as associative memories, presented by artificial neural nets. Generalization occurs when the probability of acting successfully on a previously unseen exemplar is larger than just random-guessing. This led several authors to study the ability of generalization within the framework of supervised learning [1, 2]. The simplest model where this property can be studied systematically is the linear perceptron with no hidden units. This has been done using a statistical dynamical approach [3] and through the use of equilibrium statistical mechanics [4, 5, 6, 7]. Given such fixed architecture it seems natural to try to answer questions such as what is the best possible algorithm in the sense of maximizing generalization.

The aim of this paper is to study this problem of optimal generalization algorithms, within two possible scenarios of supervised learning. In the first one, we consider the case of *single presentation of examples* or what has been called *on-line* learning or even *incremental* learning [8, 9, 10, 11, 12]. In this case each example is used sequentially, in a manner as prescribed by the learning algorithm, and then thrown away. The synaptic changes made at a given stage of the learning procedure depend specifically only on the example being presented and possibly on the current state of the net. The well known Hebb algorithm [13] for Boolean output perceptrons is a simple instance of on-line learning where all examples receives the same weight independently of the network state. Allowing a modulation mechanism on the Hebbian term has proven to be a very cheap scheme from a computational cost point of view presenting the same power law decay of the generalization error as standard iterative algorithms [10].

On-line learning is also the natural procedure for time varying rules [11, 14] where the examples might not be available all at once, or even when old examples may not be any longer representative of the present state of the rule which has to be infered. In some cases it might even reduce the 'overfitting' effect typical of some exhaustive methods [15]. It is also the natural scheme for 'learning by queries' [8, 10], since the criterium for selecting examples depends on the stage of learning. Finally, we observe that on-line learning has been extended to some multilayer networks leading to very interesting results [16, 17, 18, 19].

The second scenario of supervised learning that we will study is that of *exhaustive learning* or what might be called, by opposition, *off-line* learning. In this case the synaptic changes depend on the whole set of learning examples through a global cost function and they are used repeatedly until minimization of this cost function is achieved. In this manner the problem of learning has been presented as a problem of equilibrium statistical mechanics[2, 4].

A further distinction which appears in the case of linear perceptrons is between *constrained* and *unconstrained* learning [3]. In the former case the norm of the perceptron weight vector is maintaned constant throughout the learning procedure. In the later, this

norm can depend on the learning stage or the number of examples.

For the case of unconstrained learning our results reduce to previous findings [5, 6, 7], with perhaps a different point of view on the nature of the cost function. For the case of constrained learning, however, our results are new and give surprising results: better generalization is achieved with an *inconsistent algorithm*, that is, without minimizing the *empirical* error (the quadratic difference between the two network outputs). We show that, in this case of constrained learning, minimization of the empirical error leads to overfitting *even if the examples are noiseless*!

In the next section we present the model and discuss the performance measures. In section 3 the dynamics of on-line learning is presented and the optimal algorithm determined. The optimized dynamics can be thought of as a gradient descent method which at every time step decreases a cost (*energy*) function which depends explicitly on only the last presented example. This on-line cost function suggests a global cost function, which depends on all the examples of the learning set, to be used in an off-line manner. In section 4 the equilibrium statistical mechanics results for this energy function are obtained using the, by now standard, replica method.

The power of single presentation of examples is perhaps best illustrated by the fact that the popular quadratic error energy function with exhaustive learning, which in practice means substantial computational cost, is outperformed by the computationaly cheap optimized on-line algorithm for $\alpha$ up to $\approx 0.71$, where $\alpha$ is the number of examples per number of adjustable weights. It is outperformed by the exhaustive optimized energy function for $\alpha$ up to 1. For $\alpha > 1$ both exhaustive methods lead to perfect generalization. Section 5 presents some concluding remarks concerning our results from a point of view of maximum log-likelihood methods.

# 2 The Model

## 2.1 Learning from examples in perceptrons

The single-layer perceptron output is a function of a weighted sum of $N$ inputs,

$$\sigma_J(\mathbf{S}) = g(h)\,, h \equiv \sum_j \frac{\mathbf{J}_j \mathbf{S}_j}{\sqrt{N}} = \sqrt{N}\,\mathbf{J}\cdot\mathbf{S}\,, \tag{1}$$

where $h$ is the perceptron *local field*, $\mathbf{S} = \{S_j\}(j = 1, \ldots, N)$ is a $N$-dimensional *input vector*, $\mathbf{J} = \{J_j\}$ is the perceptron *weight vector* and the convention

$$\mathbf{X}\cdot\mathbf{Y} = \frac{1}{N}\sum_j^N X_j Y_j$$

for the scalar product of $N$-dimensional vectors has been used; $g(x)$ is the perceptron *transfer function* and it defines the type of machine under study, e.g. we may have a *linear perceptron* ($g(x) = x$), a *graded response perceptron* ($g(x)$ is a sigmoidal function like $\tanh(x)$) or a *Boolean perceptron* ($g(x) = sign(x)$).

Here we consider the *realizable* generalization task where the rule to be infered by the *student* (or *hypothesis*) perceptron $\mathbf{J}$ is the map performed by a *teacher* (or *rule*) perceptron with unknown weights $\mathbf{B} = \{B_j\}$ but the same architecture and transfer function. Then, the *training* (or *data*) set $\mathcal{L} = \{(\mathbf{S}^1, \sigma_B^1), \ldots, (\mathbf{S}^\mu, \sigma_B^\mu), \ldots, (\mathbf{S}^P, \sigma_B^P)\}$ is composed of $P = \alpha N$ input-output pairs $(\mathbf{S}^\mu, \sigma_B^\mu)$ where the input vectors have some probability measure $d\nu_{\mathcal{L}}(\mathbf{S})$ and the desired output is given by

$$\sigma_B^\mu = g(b)\,, b \equiv \sqrt{N}\,\mathbf{B}\cdot\mathbf{S}^\mu\,, \tag{2}$$

where $b$ is the *rule local field*.

Usually, the learning process is thought of as an iterative minimization (say, by gradient descent) of some cost function defined by the total data set (*off-line* learning). This presuposes the storage and repetitive presentation of the learning set (the so called learning *epochs*). However, a simpler learning process (*on-line* learning) has been considered where examples are presented only once and sequentially. The change in the perceptron weights being done along the gradient of a cost function defined only by the new example $\mu$ and the present network state $\mathbf{J}(\mu - 1)$.

## 2.2 Performace measures

Different cost functions define learning algorithms with different generalization performances. The generalization performance can be measured through the achieved correlation (or *overlap*) between the hypothesis and rule vectors, which we write as

$$\rho \equiv \frac{\mathbf{B}\cdot\mathbf{J}}{\sqrt{MQ}} = \cos\theta\,, \tag{3}$$

where $Q \equiv \mathbf{J}\cdot\mathbf{J}$ and $M \equiv \mathbf{B}\cdot\mathbf{B}$ are the student and teacher norms respectively and $\theta$ is the angle between the two $N$-dimensional vectors (see figure 1). We want to calculate the *average* value of this correlation $\rho(\alpha)$ as a function of the number of examples per degree of freedom $\alpha = P/N$.

The usual performance measure utilized in the literature is the *generalization error*

$$e_g \equiv \int d\nu_{\mathcal{T}}(\mathbf{S})\frac{1}{2}\left(b(\mathbf{S}) - h(\mathbf{S})\right)^2 = \frac{1}{2}\left(M + Q - 2\rho\sqrt{MQ}\right)\,, \tag{4}$$

where $d\nu_{\mathcal{T}}(\mathbf{S})$ is the measure of random input vectors whose components are drawn from a distribution with zero mean an unit variance. We observe that this *test set* measure $d\nu_{\mathcal{T}}$ may be not the same as the *training set* measure $d\nu_{\mathcal{L}}$.

Note that when $M$ and $Q$ are fixed (say, $M = Q = 1$ as in [4]) then maximization of $\rho$ is equivalent to minimization of $e_g$ and we have $e_g = 1 - \rho$. If, however, $Q$ also can be adjusted, then it is trivial to see from (4) that $e_g$ can be further minimized by choosing $Q$ such that $\sqrt{Q} = \rho\sqrt{M}$ (see fig. 1) giving $e_g = 1 - \rho^2$. Since $e_g$ depends not only on the angle between $\mathbf{J}$ and $\mathbf{B}$ but also on the modulus of $\mathbf{J}$ it seems to us that it is not a *complete* measure for describing the learning process because vectors $\mathbf{J}$ at different angles from the rule vector $\mathbf{B}$ will be characterized by the same $e_g$.




Figure 1: Geometrical interpretation of the learning problem: the overlap $\rho$ is the cosine of the angle $\theta$ between the vectors $\mathbf{B}$ and $\mathbf{J}$. In the constrained case (dashed) the perceptron must lie in the external circle (which represents a $N-1$ dimensional spherical surface). In the unconstrained case (solid) the optimal perceptron is found to lie in the internal surface.

We think that it is important to assign different performance measures to vectors at different angles from the rule. This is the case for Boolean perceptrons where the error measure $e_g^B$ depends univocally on $\rho$ through $e_g^B = \pi^{-1} \arccos \rho$ [2]. We observe that $e_g^B$ can also be used to characterize the linear perceptron: it measures the probability that the hypothesis produces a response with a wrong sign. Perceptrons presenting the same value for $e_g$ may have different values for $e_g^B$.

We thus prefer to concentrate our attention on the evolution of the overlap $\rho(\alpha)$ as a function of the number of examples, and to consider separately the case with constrained (that is, hypothesis norm $Q$ fixed) and unconstrained learning, as is done by Krogh and Hertz [3].

# 3 On-line Learning

## 3.1 The learning equations

A general form for on-line learning procedures can be written as

$$J_i(\mu) = \left(1 - \frac{\Omega_\mu}{N}\right) J_i(\mu - 1) + \frac{1}{N} F(\mu) S_i^\mu \,, \tag{5}$$

where $\Omega_\mu$ is a decay parameter (which we may allow to depend on the example $\mu$) and $F(\mu)$ is a function to be optimally determined later. At this point it is worth mentioning that we do not know on what variables it depends, much less its form.

From the corresponding evolution of the escalar products $R(\mu) = \mathbf{B} \cdot \mathbf{J}(\mu)$ and $Q(\mu) = \mathbf{J}(\mu) \cdot \mathbf{J}(\mu)$ we obtain a difference equation (up to order $1/N$) for the evolution of the overlap $\rho(\mu) = R(\mu)/\sqrt{Q(\mu)M}$ [10, 14]

$$\rho(\mu) = \rho(\mu - 1) + \frac{\rho(\mu)}{N} \left[ \left( \frac{1}{\rho(\mu)} \frac{b_\mu}{\sqrt{M}} - \frac{h_\mu}{\sqrt{Q}} \right) \frac{F(\mu)}{\sqrt{Q}} - \frac{I_\mu}{2} \left( \frac{F(\mu)}{\sqrt{Q}} \right)^2 \right] \,, \tag{6}$$

where $h_\mu \equiv \sqrt{N}\, \mathbf{J}(\mu - 1) \cdot \mathbf{S}^\mu$ is the hypothesis local field and $I_\mu \equiv \mathbf{S}^\mu \cdot \mathbf{S}^\mu$ is the input vector norm. Note that $h_\mu$ is defined by using the *new* example $\mu$ with the *previous* state $\mathbf{J}(\mu - 1)$.

From eq. 6 we can obtain, in the limit $N \to \infty$, a differential equation for the overlap evolution in the 'continuous' time $\alpha = \mu/N$ [8, 10, 14],

$$\frac{d\rho}{d\alpha} = \rho \left\langle \left( \frac{1}{\rho} \frac{b_\mu}{\sqrt{M}} - \frac{h_\mu}{\sqrt{Q}} \right) \frac{F(\mu)}{\sqrt{Q}} - \frac{I\mu}{2} \left( \frac{F(\mu)}{\sqrt{Q}} \right)^2 \right\rangle_\mu \,, \tag{7}$$

where $\langle \bullet \rangle$ denotes an average over the latest example. The evolution of the norm $\sqrt{Q}$ is obtained by the same procedure giving

$$\frac{dQ}{d\alpha} = 2Q \left\langle \frac{h_\mu}{\sqrt{Q}} \frac{F(\mu)}{\sqrt{Q}} + \frac{I_\mu}{2} \left( \frac{F(\mu)}{\sqrt{Q}} \right)^2 - \Omega_\mu \right\rangle_\mu \,. \tag{8}$$

These equations can be used to determine $\rho$ and $Q$ (and then $e_g$) for an specific distribution of examples for any algorithm $F$. The decay factor $\Omega_\mu$ can be used to make $dQ/d\alpha = 0$. If we start from the initial condition $Q(0) = 1$ we can mimic the spherical perceptron constraint. IF $\Omega_\mu = 0$ we have the case of unconstrained learning.

## 3.2 Optimal on-line learning procedure

From a variational analysis we find that the function $F(\mu)$ which maximizes the overlap increment per example $d\rho/d\alpha$ is

$$F_{opt}(\mu) = \frac{1}{I_\mu}\left[\frac{\sqrt{Q}}{\rho(\mu-1)}\,\frac{b_\mu}{\sqrt{M}} - h_\mu\right] . \tag{9}$$

Without loss of generality the input vector can be normalized to $I_\mu = 1$, being clear that (9) is the general optimal function when this is not the case. The optimal learning algorithm then assumes the form

$$J_i(\mu) = \left(1 - \frac{\Omega_\mu}{N}\right) J_i(\mu-1) + \frac{\sqrt{Q}}{N}\left(\frac{1}{\rho}\frac{b_\mu}{\sqrt{M}} - \frac{h_\mu}{\sqrt{Q}}\right) S_i^\mu . \tag{10}$$

We can define a cost (or *energy*) function such that the learning dynamics eq. (5) can be regarded as the instantaneous gradient descent in the space of normalized vectors $\hat{J}_i \equiv J_i/\sqrt{Q}$,

$$\hat{J}_i(\mu) = \left(1 - \frac{\Omega_\mu}{N}\right)\, \hat{J}_i(\mu-1) + \frac{1}{N}\frac{\partial E^\mu(\mathbf{J})}{\partial \hat{J}_i} , \tag{11}$$

where $E^\mu(\mathbf{J})$ is the cost function provided by example $\mu$. Since in general we may have $E^\mu$ depending on $Q(\mu-1)$, only in the case of constrained learning $Q = const$ the derivatives in $J_i$ and $\hat{J}_i$ will be equivalent.

We will show bellow that the training energy which generates the optimal function (9) can be written in the suggestive form [10, 14]

$$E^\mu_{opt}(\mathbf{J}) = -\Gamma \ln P(\sigma^\mu_B \mid h_\mu) - \Gamma \ln Z \tag{12}$$

where $Z$ is a constant, $\Gamma$ is a parameter discussed below and $P(\sigma^\mu_B \mid h_\mu)$ is the conditional probability of the new output data given the field $h_\mu$ (that is, given the present hypothesis $\mathbf{J}(\mu-1)$ and the input $\mathbf{S}^\mu$). Although irrelevant for the learning process (since it depends only on the derivative of $E^\mu_{opt}$), we conserve the constant term $Z$ for posterior discussion. This cost function is reminescent of maximum log-likelihood methods, but the new element here is the parameter

$$\Gamma = \frac{1-\rho^2}{\rho^2} = \tan^2\theta \tag{13}$$

which can be regarded as a time dependent (or better, a performance dependent [14]) *learning rate* parameter which decreases to zero as $\mathbf{J}$ gets closer to $\mathbf{B}$. Although we are in a noiseless learning case, $\Gamma$ plays the role, in a formal sense, of a temperature-like quantity and will thus be dubbed the *hypothesis temperature*, since it is zero if the hypothesis $\mathbf{J}$ is in the 'ground state' $\mathbf{B}$ and is infinite if there is no correlation between them. This 'temperature', which is

a measure of the similiarity between rule and hypothesis, should of course not be confused with the *learning temperature* usual in the literature which describes the noise level of the stochastic learning process.

We now show that the prescription given by eq. (12) leads indeed to eq. (10). Considering input vectors whose components are i.i.d. with zero mean and unit variance. The conditional probability $P(\sigma_B^\mu \mid h_\mu)$ is determined by the law of large numbers and by geometry, and depends only on $\rho$ (which is the cosine of the angle between the vectors $\mathbf{B}$ and $\mathbf{J}$. For linear perceptrons where $\sigma_B^\mu = b_\mu$ we have

$$P(b_\mu \mid h_\mu) = \frac{1}{\sqrt{2\pi(1-\rho^2)}} \exp\left(-\frac{(b_\mu/\sqrt{M} - \rho h_\mu/\sqrt{Q})^2}{2(1-\rho^2)}\right) . \tag{14}$$

Introducing in eq. (12) we obtain the desired cost function

$$E_{opt}^\mu(\mathbf{J}) = \frac{1}{2}\left(\frac{1}{\rho(\mu)}\frac{b_\mu}{\sqrt{M}} - \frac{h_\mu}{\sqrt{Q}}\right)^2 , \tag{15}$$

if we use (12) with $Z = (2\pi(1-\rho^2))^{1/2}$. Note that the original dynamics (10) is recovered only after changing from the $\hat{\mathbf{J}}$ to the $\mathbf{J}$ variables, which imply the appearance of a $Q$ term necessary to one get the expression for $F(\mu)$, eq. (9). This energy function naively resembles the standard quadratic error function, but the $1/\rho$ factor has a non negligible effect which leads to improved performances[1].

## 3.3 Optimal performance for uniform distributions

We consider now the cases where the components of $\mathbf{S}$ are drawn from an uniform distribution in the hipercube $\{\pm 1\}^N$ or from a Gaussian distribution with zero mean and unit variance. We have $\langle b^2\rangle = M$, $\langle h^2\rangle = Q$ and $\langle bh\rangle = \rho\sqrt{MQ}$, leading to the simple differential equations

$$\frac{d\rho}{d\alpha} = \frac{1-\rho^2}{2\rho} , \tag{17}$$

$$\frac{dQ}{d\alpha} = Q\left(\frac{1-\rho^2}{\rho^2}\right) - 2Q\Omega . \tag{18}$$

[1] We observe that the cost function prescription (12) is also valid for boolean perceptrons, enabling a unified approach to the generalization problem. In the boolean case we have $Z = 1$ and

$$E_{opt}^\mu = -\Gamma \ln P(\sigma_B^\mu \mid h_\mu) = -\Gamma \ln H\left(\frac{-\sigma_B^\mu h_\mu}{\sqrt{Q}\sqrt{\Gamma}}\right), \qquad H(x) \equiv \int_x^\infty \frac{dt}{\sqrt{2\pi}} e^{-t^2/2} . \tag{16}$$

This case has been studied in our previous works [10, 14].

where we assumed $\Omega$ constant. Note that the equation for $\rho$ is now decoupled from the equation for $\sqrt{Q}$ and can be directly integrated leading to

$$\rho_{opt}(\alpha) = \sqrt{1 - e^{-\alpha}} \,. \tag{19}$$

This is a theoretical upper bound for $\rho(\alpha)$ for any algorithm used in *on-line* mode. In this form it does not correspond to a *practical* algorithm because the optimal function $F$ given by eq. (9) depends on the unknow parameters $M$ and $\rho$. The form for the optimal weight function suggests that we should estimate (in an on-line manner) these parameters from the data set. A possible way to do this will be discussed in the next section, and by now we will assume the simpler case, usual in the literature, where $M$ is know.

In the case of *constrained* learning $Q = M = 1$ the algorithm can be used by substituting in a self-consistent manner the value $\rho(\mu)$ by the theoretical value $\rho(\alpha)$. The optimal function is then

$$F_{opt}^{online} = \frac{b_\mu}{\sqrt{1 - \exp(-\alpha)}} - h_\mu \,. \tag{20}$$

For *unconstrained* learning ($\Omega_\mu = 0$) we can write eq. (18) as

$$\frac{d}{d\alpha}\sqrt{Q} = \frac{\sqrt{Q}}{\rho}\,\frac{d\rho}{d\alpha} \,. \tag{21}$$

By appropriately choosing the *tabula rasa* $Q(0) = 0$ as initial condition, we have $\sqrt{Q} = c\rho$ for some constant $c$ which can be set to one. In this case an approximation of the optimal algorithm will be $F = (\hat{b} - h)$, that is, the optimal algorithm for unconstrained learning reduces to the standard one (with a pre-normalization of the data $\hat{b} = b/\sqrt{M}$).

It is important to stress the fact that the distribution of examples $P(\mathbf{S})$ was used to calculate the corresponding evolution of the overlap $\rho(\alpha)$ but it is not necessary to know it exactly in order to determine the optimal on-line algorithm eq. (9), which depends on the less specific conditional probability $P(b|h)$. Several distributions $P(\mathbf{S})$ can generate the same conditional distribution $P(b|h)$ with, say, different forms for $P(h)$. In the case of Boolean perceptrons the distribution $P(h)$ affects the evolution of $\rho(\alpha)$ and controlling it may be a good learning strategy (*learning by queries* [10, 14]). It is easy to show from eq. (7) that, in the case of linear perceptrons, selection of examples leads to no improvement.

## 3.4 The standard algorithm

The same calculation can be done for the standard algorithm which uses

$$F(\mu) = b_\mu - h_\mu \,, \tag{22}$$




Figure 2: Asymptotical overlap $\rho_{max}$ as a function of the parameter $M/Q$.

leading to

$$\frac{d\rho}{d\alpha} = \sqrt{M/Q} - \rho\,\frac{M/Q+1}{2}\,. \tag{23}$$

The specific learning curve depends on the ratio $M/Q$. The overlap stops increasing ($d\rho/d\alpha = 0$) for the maximum value

$$\rho_{\max} = \frac{2\sqrt{M/Q}}{1+M/Q}\,, \tag{24}$$

The standard algorithm produces $\rho_{\max} = 1$ only when $Q = M$ (se fig. 2), contrasting with the optimal procedure which achieves $\rho = 1$ even for unrealizable tasks where $Q \neq M$. The corresponding asymptotical values ($\alpha \to \infty$) for the generalization error are

$$\begin{aligned} e_g^{\infty}(standard) &= \frac{1}{2}\frac{(M-Q)^2}{M+Q}\,, \\ e_g^{\infty}(optimal) &= \frac{1}{2}\left(\sqrt{M}-\sqrt{Q}\right)^2 \\ e_g^{\infty}(standard) &= \left(1+\frac{2\sqrt{MQ}}{M+Q}\right)\, e_g^{\infty}(optimal) \end{aligned} \tag{25}$$

Even in the realizable case ($Q = M = 1$), we obtain for the standard algorithm the obviously worst result

$$\rho = 1 - e^{-\alpha} = \rho_{opt}^2\,. \tag{26}$$

By choosing an appropriate decay factor $\Omega_\mu$, the norm $Q$ can be hold constant, say $Q = M = 1$, enabling a comparison with the results for off-line learning in a spherical perceptron. The equilibrium properties for the standard algorithm $\mathcal{E} = \frac{1}{2}\sum_\mu^{\alpha N}(b_\mu - h_\mu)^2$ has been obtained previously by Seung et al. [4]. The overlap achieved after $\alpha N$ examples is

$$\rho(\alpha) = \begin{cases} \alpha & \text{if } \alpha \leq 1 \\ 1 & \text{if } \alpha > 1 \end{cases} , \tag{27}$$

which clearly is not optimal since the result for optimal on-line learning eq. (19) gives, for small $\alpha$,

$$\rho_{opt} \approx \sqrt{\alpha} + O(\alpha) . \tag{28}$$

In figure 3 we compare the overlap produced by the various algorithms. **It is very interesting that optimal** *on-line* **learning, with a negligible computational cost, presents better results than** *off-line* **learning with the standard algorithm up to** $\alpha \approx 0.71$.




Figure 3: Overlap $\rho(\alpha)$ versus number of examples: optimal algorithm (solid) and standard algorithm (dashes). Upper curves for off-line and lower curves for on-line learning.

Concerning specifically to on-line learning procedures, the bounds obtained above are also valid for the graded response perceptrons, since in this case the optimal algorithm utilizes

the weight function

$$F(\mu) = \sqrt{\frac{Q}{M}}\,\frac{1}{\rho} g^{-1}(\sigma_B^\mu) - h_\mu \,. \tag{29}$$

where $g(x)$ is the perceptron transfer function. Recently, Biehl and Schwarze [17] obtained an asymptotical decay ($\alpha \to \infty$)

$$1 - \rho \propto e^{-0.66\alpha} \tag{30}$$

for on-line learning with the standard quadratic algorithm with an optimized learning step, which must be compared with the lower bound given by eq. (19)

$$1 - \rho_{opt} \approx \frac{1}{2} e^{-\alpha} \,. \tag{31}$$

### 3.5 Practical algorithms for stationary and drifting rules

By *practical* algorithms we mean procedures which depend only on accessible quantities. Here we examine if the optimal performance can be approximated by some practical learning algorithm. The optimal function $F$ is given by

$$F(\mu) = \frac{1}{I_\mu}\left[\frac{\sqrt{Q(\mu-1)}}{\rho(\mu-1)}\,\frac{b_\mu}{\sqrt{M}} - h_\mu\right] \,. \tag{32}$$

For stationary rules we have already observed that the dependence on $\rho$ can be lifted if we use in the optimal function $F$ the theoretical $\rho(\alpha)$ given by eq. (19) instead of the 'true' (and inacessible) value $\rho(\mu)$. For non-stationary rules we can use the approach utilized in [14] and approximate the parameter $\rho\sqrt{M/Q}$ by using eq. (4)

$$\frac{\rho\sqrt{M}}{\sqrt{Q}} = \frac{1 + M/Q}{2} - \hat{e}_g/Q \,, \tag{33}$$

with an on-line estimator for the generalization error

$$\hat{e}_g(\mu) = (1 - \frac{\omega_e}{N})\,\hat{e}_g(\mu-1) + \frac{\omega_e}{N}\,\epsilon_\mu, \qquad\qquad \epsilon_\mu = \frac{1}{2}(b_\mu - h_\mu)^2 \,. \tag{34}$$

The constant $\omega_e$ is an integration time which, from previous findings [14] and numerical simulations, we suggest to be used with the value $\omega_e \approx 2$ for a good compromise between accumulating enough data for reliable statistics and minimizing the lag from the drifiting rule produced by a large integration time. The norm $Q$ is a measurable (although non-local) quantity. In the case of an unknown teacher lenght, the dependence on $M$ can be remediated by using the *on-line* estimator

$$\hat{M}(\mu) = (1 - \frac{\omega_B}{N})\,\hat{M}(\mu-1) + \frac{\omega_B}{N}\,b_\mu^2 \tag{35}$$

for the true value of $M$. If we use $\omega_B = 1/\alpha$ we have effectively that $\hat{M}(\mu)$ is an estimative of the teacher lenght $M$ calculated from the entire learning set. If we use a constant $\omega_B$ the average is done only over a time span so that the estimator can be used, with the aid of the previous estimator $\hat{e}_g$, for the tracking of a drifting rule $\mathbf{B}$ which changes not only its direction but also its lenght.

Althought somewhat involved, the above estimative procedure provides not only a method for using the optimal algorithm but also gives a very interesting robustness to the perceptron behaviour. There is no separation between trainning and performance phases, the estimator $\hat{e}_g$ for the generalization error being a vigilance parameter which detects changes in the enviroment and increases the 'attention' function F through the parameter $\rho(\hat{e}_g)$.

Along with the versatility of incremental learning (which naturally forgets old examples no longer representative of the actual enviroment $\mathbf{B}$) this model provides a simple and analytically solvable example of an artificial neural network behaving as a truly *adaptive* system (and not only as a parametric one). Since it has been demonstrated recently [16, 17, 18, 19] that on-line learning is effective for multilayer machines, we expect that future on-line adaptive multilayer nets constructed from the same principles will substitute the traditional off-line backpropagation nets for real world problems with changing enviroments.

# 4 Off-line Learning

## 4.1 The statistical mechanics approach

Now we present the calculation for off-line learning with a global energy function defined over the whole learning set that is suggested by the on-line results of the previous section. The statistical mechanics approach [4] considers a stochastic version of the learning algorithm

$$J_i(t+1) = J_i(t) + \frac{1}{N}\frac{\partial V(\mathbf{J})}{\partial J_i} + \frac{1}{N}\frac{\partial E(\mathbf{J})}{\partial J_i} + \frac{1}{\sqrt{N}}\,\eta_i(t)\,, \tag{36}$$

where white noise with variance $< \eta.\eta >= 2T$ have been added, $E(\mathbf{J})$ is the cost function specific for each algorithm and $V(\mathbf{J})$ is a potential which assures the spherical normalization. The index $t$ denotes a complete presentation of the learning set (often called a *training epoch*).

It is well know that this Langevin equation leads, in equilibrium, to a Gibbs distribution for the variables $\{J_i\}$. The partition function is

$$Z_{\mathcal{L}} = \int d\nu(\mathbf{J})\, e^{-\beta E(\mathbf{J})}\,, \tag{37}$$

where $\beta = 1/T$ ($T$ is usually called the *learning temperature*). The measure $d\nu(\mathbf{J})$ reffers to the *a priori* distribution produced by $V(\mathbf{J})$ which, in the case of spherical contraint $\mathbf{J}\cdot\mathbf{J} = Q$,

reads

$$d\nu(\mathbf{J}) = \left(\prod_i^N \frac{dJ_i}{\sqrt{2\pi e Q}}\right) \ \delta\left(\sum_i^N J_i^2 - QN\right). \tag{38}$$

The Gibbs distribution is used to perform averages over the *a posteriori* distribution of the weights, the *thermal averages* denoted by $\langle \bullet \rangle_T$. Since this distribution, and so the partition function, still depends on the specific realization of the learning set $\mathcal{L}$ (which is a set of random quenched variables), we need to perform a *quenched* average over the possible learning sets by using the *replica method*. The formalism of replicas is by now standard [1, 2, 4] and we present only the results.

Our calculations will be done for a training energy suggested by the optimal on-line algorithm,

$$E(\mathbf{J}, r) = \frac{1}{2}\sum_{\mu=1}^{\alpha N}\left(\frac{\sqrt{Q}}{\sqrt{M}r(\alpha)}b_\mu - h_\mu\right)^2, \tag{39}$$

where the parameter $r(\alpha)$, which if our prescription (12) is correct will be found to be the overlap $\rho(\alpha)$, is by now considered an arbitrary function to be optimized at the final stage of our calculations.

The replica formalism is very attractive because the order parameters which appear in the calculations

$$R_a = \langle \mathbf{J}^a \cdot \mathbf{B}\rangle_T, \qquad Q_{ab} = \langle \mathbf{J}^a \cdot \mathbf{J}^b\rangle_T \tag{40}$$

have a natural interpretation in the learning problem. The first is the (non-normalized) average overlap between the hypothesis and the rule perceptrons and the second is the typical overlap between two possible hypothesis or students; $a$ and $b$ are replica indeces.

## 4.2 Replica symmetric results

If we assume *replica symmetry*

$$R_a = R, \qquad Q_{ab} = Q\delta_{ab} + q(1-\delta_{ab}), \tag{41}$$

which is a valid assumption for the case of noiseless examples [7], we obtain the free energy density as

$$-\beta f = \frac{1}{2}\left[\ln(1-q/Q) + \frac{q - R^2/M}{Q-q} - \alpha\ln\left(1+\beta(Q-q)\right) - \alpha\beta\,\frac{q + Q/r^2 - 2R\sqrt{Q/Mr^2}}{1+\beta(Q-q)}\right] \tag{42}$$

It is useful to write the free energy as a function of the normalized quantities

$$\rho = \frac{R}{\sqrt{QM}}, \qquad \tilde{q} = \frac{q}{Q}, \qquad \tilde{\beta} = \frac{Q}{T} = \frac{1}{\tilde{T}} \tag{43}$$

which are the hypothesis-rule overlap, the inter-hypothesis overlap and the ratio between the noise variance and the weight vector lenght respectively. The relative quantity $\tilde{T}$ is clearly the relevant measure of the 'temperature', and not the absolute noise variance itself. The free energy assumes the more transparent form

$$-\tilde{\beta}\frac{f}{Q} = \frac{1}{2}\left[\ln(1-\tilde{q}) + \frac{\tilde{q}-\rho^2}{1-\tilde{q}} - \alpha\ln\left(1+\tilde{\beta}(1-\tilde{q})\right) - \alpha\tilde{\beta}\,\frac{\tilde{q}+1/r^2-2\rho/r}{1+\tilde{\beta}(1-\tilde{q})}\right] . \tag{44}$$

The order parameters $\rho$ and $\tilde{q}$ are given by the saddle point equations $\partial f/\partial\rho = 0$ and $\partial f/\partial\tilde{q} = 0$. After a simple algebra we obtain

$$\rho = \frac{\alpha}{r}\,\frac{x}{1+x}\,, \tag{45}$$

$$\tilde{q} = \frac{\alpha}{r^2}\,\frac{x^2}{(1+x)^2-\alpha x^2}\,\left[1-\alpha\frac{(x-1)}{(x+1)}\right]\,, \tag{46}$$

with the shorthand $x = \tilde{\beta}(1-\tilde{q})$.

In the limit of zero learning temperature ($x \to \infty$) we obtain simply

$$\rho = \frac{\alpha}{r}, \qquad \tilde{q} = \frac{\alpha}{r^2}\,. \tag{47}$$

### 4.3 The effect of the parameter $r(\alpha)$

The correlation between hypothesis depends on the function $r(\alpha)$ utilized in the algorithm, and $\rho(\alpha)$ can be optimized if we choose the minimal $r(\alpha)$ possible. Since the maximum value for the overlap between the hypothesis is $\tilde{q} = 1$, we find

$$r_{opt}(\alpha) = \sqrt{\alpha}\,, \tag{48}$$

which leads to

$$\rho_{opt}(\alpha) = \sqrt{\alpha}\,. \tag{49}$$

It is important to observe that the same result may be obtained if we extremize $f$ with respect to $r$. The condition $\partial f/\partial r = 0$ gives directly $r_{opt} = \rho$!

The result $r_{opt}(\alpha) = \rho_{opt}(\alpha)$ corroborates our prescription (12) derived from the optimal on-line algorithm. We conjecture that this prescription leads, indeed, to an optimal off-line algorithm, althought this has not been rigourously proven. By now, we will call this algorithm as the 'optimal' one (within commas). The value $\tilde{q} = 1$ means that there is only one 'optimal' generalization vector which is determined by the learning set. Seung et al. [4], in contrast, obtain that $\tilde{q} = \alpha M/Q$ for the overlap between the hypothesis produced by the standard algorithm (which is obtained using $r = \sqrt{Q/M}$). We observe that all these results are valid for $\alpha < 1$. For $\alpha > 1$ we have perfect generalization $\rho = 1$.

It is curious that in both the off-line and on-line cases the simple relation $\rho_{opt} = \sqrt{\rho}$ emerges, where $\rho_{opt}$ is the 'optimal' algorithm result, while $\rho$ is the result obtained by using the empirical error as cost function. A similar relation $\rho_{Bayes} = \sqrt{\rho}$ occurs in the case of a boolean perceptron [20] between the optimal 'Bayes' overlap and that obtained by the 'Boltzmann' algorithm for $T = 0$. Boltzmann algorithm also minimizes the empirical error

$$\mathcal{E} = \sum_{\mu=1}^{\alpha N} \Theta(-\sigma_B^\mu \sigma_J^\mu) = \frac{1}{4} \sum_{\mu=1}^{\alpha N} (\sigma_B^\mu - \sigma_J^\mu)^2 \,, \tag{50}$$

being very similar to the standard algorithm for the linear case. Both are called *consistent* algorithms in the literature [21] because they produces zero error in the training set. It is important to note that the optimized algorithm does not minimizes the empirical error, $\mathcal{E}$ being non zero even for $T = 0$ and, as is our case, for noiseless examples (it is an *inconsistent* algorithm).

In the case of unconstrained learning [3, 5, 7] there is an obvious choice for the perceptron norm $J(\alpha)$ which minimizes the distance $\mathbf{D} = \mathbf{B} - \mathbf{J}$. This condition is represented in figure 1 by the internal circle, where $\sqrt{Q(\alpha)} = \sqrt{M}\cos\theta = \sqrt{M}\rho$. In this case (but only in this case!) the 'optimal' algorithm eq.(39) coincides with the standard one, producing the so called pseudo-inverse solution which has the same $\rho = \sqrt{\alpha}$ behavior. We observe that in the case of *constrained* learning the solution vector (which we have found to be unique) lies in the direction of the pseudoinverse vector, differing only in its lenght.

The behaviour for $T > 0$ requires some lengthy discussion and will be reported elsewhere.

# 5 Conclusions

The off-line learning algorithm suggested by the optimal on-line procedure is equivalent to a synaptic dynamics that minimizes the cost function

$$E(\mathbf{J}, t)/Q = \alpha N \left[ \Gamma \frac{1}{\alpha N} \sum_{\mu=1}^{\alpha N} (-\ln P(b_\mu \mid h_\mu)) - \Gamma \ln Z \right] = \sum_{\mu=1}^{\alpha N} \left( \frac{b_\mu}{\rho(t)\sqrt{M}} - \frac{h_\mu}{\sqrt{Q}} \right)^2 , \tag{51}$$

where $\Gamma(t) = (1 - \rho^2(t))/\rho^2(t)$. We can estimate $\rho(t)$ by some method or, if we are interested only in the equilibrium performance (without caring about learning times), we can use the equilibrium value $\rho(t \to \infty) = \sqrt{\alpha}$ as have been done in the previous section.

This can be regarded as a maximum log-likelihood method with an optimally decreasing learning rate $\Gamma(t)$. But if we consider the function $E(\mathbf{J}, t)$ as the *true* cost function (that is, $\Gamma(t)$ being an *essential* part of the algorithm), then this cost function is more an energy-like than an entropy-like quantity as usually regarded in the optimization literature.

The parameter $\Gamma$ has a non-negligible effect in the on-line case. However, since the effect of a learning step vanishes for the *equilibrium properties* when minimizing a cost function,

the above considerations (entropy versus energy interpretation) would seem to be irrelevant for the off-line case. An interesting possibility suggested by the above results is, however, that even for exhaustive learning, the step parameter has a non-trivial effect in the *learning times*. We conjecture that the minimal characteristic learning time (a lower bound) will be obtained by using a learning rate given by $\Gamma(t)$. This eventually may be confirmed by using the dynamical approach of Krogh and Hertz [3]. If this is true, these results suggest rethinking maximum-likelihood methods by incorporating the learning rate parameter (the 'hypothesis temperature') as an essential and non-trivial component of the cost function $E_\rho$ which has 'energy' (and not 'entropy') as its physical analogue.

Finally we stress the fact that we have presented a simple and clear example where the naive minimization of the empirical error leads to overfitting even with noise-free data. The 'optimal' algorithm is an inconsistent one (its empirical error is always non zero), but has better generalization than consistent algorithms. We have also shown that the proper choice of the cost function leads to an on-line performance better (for $\alpha < 0.71$) than the brute force off-line learning of standard algorithms. These results are consistent with previous findings on the generalization properties of Boolean perceptrons [10]. We expect that results like this will also hold for richer network architectures than the single layer perceptron.

**Acknowledgements** OK and NC received support from the Brazilian agency CNPq.

# References


[1] Hertz J A, Krogh A and Palmer R G, *Introduction to the Theory of Neural Computation* (Addison-Wesley, Redwood City, CA, 1991).

[2] Watkin T L H, Rau A and Biehl M 1993 *Rev. Mod. Phys.* **65** 499.

[3] Krogh A and Hertz J A 1992 *J. Phys. A: Math. Gen.* **25** 1135.

[4] Seung S Sompolinsky H and Tishby N 1992 *Phys. Rev. A* **45** 6056.

[5] Bös S, Kinzel W and Opper M 1993 *Phys. Rev. E* **47** 1384.

[6] Dunmur A P and Wallace D J 1993 *J. Phys. A: Math. Gen.* **26** 5767.

[7] Fontanari J F 1993 *J. Phys. A: Math. Gen.* **26** 6147.

[8] Kinzel W and Rujan P 1990 *Europhys. Lett.* **13** 473.

[9] Kinouchi O and Caticha N 1992 *Physica A* **185** 411.

[10] Kinouchi O and Caticha N 1992 *J. Phys. A: Math. Gen.* **25** 6243.

[11] Biehl M and Schwarze H *J. Phys. A: Math. Gen* **26** 2651.

[12] Biehl M and Schwarze H 1994 Learning by Online Gradient Descent, Preprint Institut für Theoretische Physik, Universität Würzburg.

[13] Vallet F and Cailton J-G 1990 *Phys. Rev. A* **41** 3059.

[14] Kinouchi O and Caticha N 1993 *J. Phys. A: Math. Gen.* **26** 6161.

[15] Kinouchi O and Caticha N 1995 Preventing Overfitting by Online Learning, in preparation.

[16] Kabashima Y 1994 *J.Phys. A:Math. Gen.* **27** 1917.

[17] Biehl M and Riegler P 1994 *Europhys. Lett.* **28** 525.

[18] Copelli M and Caticha N 1995 On-line learning in the Committee Machine, accepted for publication in *J.Phys. A: Math. Gen.*.

[19] Copelli M, Kinouchi O and Caticha N 1995 Equivalence Between On-line Learning in Perceptrons with Noisy Examples and Committee Machines, submited to *J. Phys. A: Math Gen.*

[20] Opper M and Haussler 1991 *Phys. Rev. Lett.* **66** 2677.

[21] Fontanari J F and Meir R 1992 *Phys. Rev. A* **45** 8874.