On the Computational Power of Noisy Spiking Neurons

Wolfgang Maass

Institute for Theoretical Computer Science, Technische Universitaet Graz
Klosterwiesgasse 32/2, A-8010 Graz, Austria, e-mail: maass@igi.tu-graz.ac.at

Abstract

This article provides some first results about the computational power of neural networks that are based on a neuron model which is acceptable to many neurobiologists as being reasonably realistic for a biological neuron.

Biological neurons communicate via spike-trains, i.e. via sequences of stereotyped pulses ("spikes") that encode information in their time-differences ("temporal coding"). In addition it is wellknown that biological neurons are quite "noisy", i.e. the precise times when they "fire" (and thereby issue a spike) depend not only on the incoming spike-trains, but also on various types of "noise".

It has remained unknown whether one can in principle carry out reliable digital computations with noisy spiking neurons. This article presents rigorous constructions for simulating in real-time arbitrary given boolean circuits and finite automata with arbitrarily high reliability by networks of noisy spiking neurons.

In addition we show that with the help of "shunting inhibition" such networks can simulate in real-time any McCulloch-Pitts neuron (or "threshold gate"), and therefore any multilayer perceptron (or "threshold circuit") in a reliable manner. These constructions provide a possible explanation for the fact that biological neural systems can carry out quite complex computations within 100 msec.

It turns out that the assumption that these constructions require about the shape of the EPSP's and the behaviour of the noise are surprisingly weak.

1 Introduction

We consider networks that consist of a finite set V of *neurons*, a set $E \subseteq V \times V$ of *synapses*, a *weight* $w_{u,v} \geq 0$ and a *response function* $\varepsilon_{u,v} : \mathbf{R}^+ \to \mathbf{R}$ for each synapse $\langle u, v \rangle \in E$ (where $\mathbf{R}^+ := \{x \in \mathbf{R} : x \geq 0\}$), and a *threshold function* $\Theta_v : \mathbf{R}^+ \to \mathbf{R}^+$ for each neuron $v \in V$.

If $F_u \subseteq \mathbf{R}^+$ is the set of *firing times* of a neuron u, then the *potential* at the trigger zone of neuron v at time t is given by $P_v(t) := \sum_{u\,:\,\langle u,v\rangle \in E} \sum_{s \in F_u : s < t} w_{u,v} \cdot \varepsilon_{u,v}(t-s)$. The threshold function $\Theta_v(t-t')$ quantifies the "reluctance" of v to fire again at time t, if its last previous firing was at time t'. We assume that $\Theta_v(0) \in (0, \infty)$, $\Theta_v(x) = \infty$ for $x \in (0, \tau_{ref}]$ (for some constant $\tau_{ref} > 0$, the "absolute refractory period"), and $\sup\{\Theta_v(x) : x \geq \tau\} < \infty$ for any $\tau > \tau_{ref}$.

In a *deterministic* model for a spiking neuron (Maass, 1995a, b) one can assume that a neuron v fires exactly at those time points t when $P_v(t)$ reaches (from below) the value $\Theta_v(t-t')$. We consider in this article a biologically more realistic model, where as in (Gerstner, van Hemmen, 1994) the size of the difference $P_v(t) - \Theta_v(t-t')$ just governs the *probability* that neuron v fires.

The choice of the exact firing times is left up to some unknown stochastic processes, and it may for example occur that v does *not* fire in a time interval I during which $P_v(t) - \Theta_v(t-t') > 0$, or that v fires "spontaneously" at a time t when $P_v(t) - \Theta_v(t-t') < 0$. We assume that (apart from their communication via potential changes) the stochastic processes for different neurons v are independent. It turns out that the assumptions that one has to make about this stochastic firing mechanism in order to prove our results are surprisingly weak. We assume that there exist two arbitrary functions $L, \mathcal{U} : \mathbf{R} \times \mathbf{R}^+ \to [0,1]$ so that $L(\Delta,\ell)$ provides a *lower* bound (and $\mathcal{U}(\Delta,\ell)$ provides an *upper* bound) for the probability that neuron v fires during a time interval I of length ℓ with the property that $P_v(t) - \Theta_v(t-t') \geq \Delta$ (respectively $P_v(t) - \Theta_v(t-t') \leq \Delta$) for all $t \in I$ up to the next firing of v (t' denotes the last firing time of v *before* I). We just assume about these functions L and $\mathcal{U}$ that they are non-decreasing in each of their two arguments (for any fixed value of the other argument), that $\lim_{\Delta \to -\infty} \mathcal{U}(\Delta,\ell) = 0$ for any fixed $\ell > 0$, and that $\lim_{\Delta \to \infty} L(\Delta,\ell) > 0$ for any fixed $\ell \geq R/6$ (where R is the assumed length of the rising segment of an EPSP, see below). The neurons are allowed to be *"arbitrarily noisy"* in the sense that the difference $\lim_{\Delta \to \infty} L(\Delta,\ell) - \lim_{\Delta \to -\infty} \mathcal{U}(\Delta,\ell)$ can be arbitrarily small. Hence our constructions also apply to neurons that exhibit persistent firing failures, and they also allow for synapses that fail with a rather high probability. Furthermore a detailed analysis of our constructions shows that we can relax the somewhat dubious assumption that the noise-distributions for different neurons are independent. Thus we are also able to deal with "systematic noise" in the distribution of firing times of neurons in a pool (e.g. caused by changes in the biochemical environment that simultaneously affect *many* neurons in a pool).

It turns out that it suffices to assume only the following rather weak properties of the other functions involved in our model:

1) Each response function $\varepsilon_{u,v} : \mathbf{R}^+ \to \mathbf{R}$ is either excitatory or inhibitory (and for the sake of biological realism one may assume that each neuron u induces only one type of response). All excitatory response functions $\varepsilon_{u,v}(x)$ have the value 0 for $x \in [0, \Delta_{u,v})$, and the value $\varepsilon^E(x - \Delta_{u,v})$ for $x \geq \Delta_{u,v}$, where $\Delta_{u,v} \geq 0$ is the *delay* for this synapse between neurons u and v, and ε^E is the common shape of all excitatory response functions ("EPSP's"). Corresponding assumptions are made about the inhibitory response functions ("IPSP's"), whose common shape is described by some function $\varepsilon^I : \mathbf{R}^+ \to \{x \in \mathbf{R} : x \leq 0\}$.

2) ε^E is continuous, $\varepsilon^E(0) = 0$, $\varepsilon^E(x) = 0$ for all sufficiently large x, and there exists some parameter $R > 0$ such that ε^E is non-decreasing in $[0, R]$, and some parameter $\rho > 0$ such that $\varepsilon^E(x + R/6) \geq \rho + \varepsilon^E(x)$ for all $x \in [0, 2R/3]$.

3) $-\varepsilon^I$ satisfies the same conditions as ε^E.

4) There exists a source BN^- of negative *"background noise"*, that contributes to the potential $P_v(t)$ of each neuron v an additive term that deviates for an arbitrarily long time interval by an arbitrarily small percentage from its average value $w_v^- \leq 0$ (which we can choose). In section 3 we will assume in addition the availability of a corresponding *positive* background noise BN^+ with average value $w_v^+ \geq 0$.
[In a biological neuron v one can interpret these as the combined effect of a continuous bombardment with a very large number of IPSP's (EPSP's) from randomly firing neurons that arrive at remote synapses on the dendritic tree of v.]

We assume that *we* can choose the values of delays $\Delta_{u,v}$ and weights $w_{u,v}, w_v^+, w_v^-$. We refer to

all assumptions specified in this section as our *"weak assumptions"* about noisy spiking neurons. It is easy to see that the most frequently studied *concrete* model for noisy spiking neurons, the *spike response model* (Gerstner and van Hemmen, 1994) satisfies these weak assumptions, and is hence a special case. However not even for the more concrete spike response model (or any other model for noisy spiking neurons) there exist any rigorous results about *computations* in these models. In fact, one may view this article as being the first that provides results about the computational complexity of neural networks for a neuron model that is acceptable to many neurobiologistis as being reasonably realistic.

In this article we only address the problem of reliable *digital* computing with noisy spiking neurons. For results about analog computations with noisy spiking neurons we refer to the forthcoming article Maass, 1995c.

2 Simulation of Boolean Circuits and Finite Automata with Noisy Spiking Neurons

Theorem 1: *For any deterministic finite automaton D one can construct a network $N(D)$ consisting of any type of noisy spiking neurons that satisfy our weak assumptions, so that $N(D)$ can simulate computations of D of any given length with arbitrarily high probability of correctness.*

Idea of the ***proof:*** We can sketch here only some of the ideas of this rather long and technically involved proof. Since the behaviour of a *single* noisy spiking neuron is completely unreliable, we use instead *pools* $A, B, \ldots$ of neurons as the basic building blocks in our construction, where all neurons v in the same pool receive the same "input potential" $P_v(t)$. The intricacies of our stochastic neuron model allow us only to employ a *"weak coding"* of bits, where a "1" is represented by a pool A during a time interval I, if at least $p_1 \cdot |A|$ neurons in A fire (at least once) during I (where $p_1 > 0$ is a suitable constant), and "0" is represented if at most $p_0 \cdot |A|$ firings of neurons occur in A during I, where p_0 with $0 < p_0 < p_1$ is another constant (that can be chosen arbitrarily small in our construction). One can carry out *some* digital computation steps with regard to this weak coding, since if for example pool A represents a "1" during a time interval I of length $R/3$, this will raise (respectively lower) by our assumptions on ε^E and ε^I throughout a slightly later time interval J of length $R/3$ the potential $P_v(t)$ of the neurons v of another pool B to which A sends EPSP's (IPSP's). If the resulting potential $P_v(t)$ in the neurons of pool B (which may also receive EPSP's or IPSP's from other pools besides A) is sufficiently positive (negative) throughout such time interval J, one can employ our assumptions about the functions L and $\mathcal{U}$ together with the well-known Chernoff-bound (see e.g. Appendix A in (Alon et al., 1992)) in order to show that B represents a "1" ("0") during J (with arbitrarily high probability, if B is chosen sufficiently large). We choose in our constructions the considered time intervals $I, J, \ldots$ to be rather short, since on the basis of our weak assumptions (see 2), 3)) we can only employ structural information about the *initial* phase of EPSP's and IPSP's.

The described coding scheme is *weak* since it provides no useful *upper* bound (e.g. $1.5 \cdot p_1 \cdot |A|$) on the number of neurons that fire during I if A represents a "1" (nor on the number of firings of a single neuron in A). It also does not impose constraints on the *exact timing* of firings in A *within* I. The latter is relevant, since an "accidental" *simultaneous* firing of many neurons in A may create a higher potential-peak in other neurons (and could thereby make for a moment

their firing probability unusually high). However we are not able to guarantee more detailed information about the firing states of pools in the here considered context. These difficulties make it for example impossible to simulate in a direct manner an AND-gate by pools A, A' and B of neurons (where the firing activity in B during interval J should represent a "1" if and only if the firing activities of both A and A' during a preceding interval I represented a "1"). We cannot avoid that a "1" from A alone might generate a "1" in B through an unusually large potential-peak, although the activity of A' during interval I represented a "0".

In order to synchronize various parallel computations in $N(D)$, and to "refresh" the representations of "1" during the computation, we employ a pacemaker PM. PM sends sharp "potential waves" (consisting of staggered EPSP's and IPSP's) to other neurons v. Each such wave raises the potential for a time period of length $\leq R/2$, and for the interval of length $R/6$ in the middle of that period it raises the potential by some guaranteed amount. PM consists of pools A and B that send volleys of EPSP's to each other, together with auxiliary pools of inhibitory neurons that halt the resulting high firing activity in A respectively B within a time interval of length $R/2$ after its beginning. We construct PM in such a way that we can *prove* that it does its job (with arbitrarily high probability) for a given number of cycles. For that purpose one has to wait with the next period of high firing activity in pool A (B) until all EPSP's and IPSP's from the previous cycle have expired. We are however not able to prevent random fluctuations of the cycle time of PM by up to $R/3$ at each cycle (unless we make further assumptions about the neurons), but with suitable precautions this can be tolerated for the computation of $N(D)$. Although we are able to show that the described firing pattern can be *preserved* in PM, we have to *assume* that it is initially induced at the beginning of the computation (e.g. via a quickly rising potential wave) from the outside.

We would like to point out that one replace the "oscillator" PM by a synfire chain, if the latter is viewed as being biologically more plausible.

Since we are able to synchronize subcomputations in $N(D)$ with the help of PM, we can employ in $N(D)$ multiple copies of the subsequently described module for a NOR-gate. In this way $N(D)$ can compute any desired boolean function (in particular the transition function of the DFA D). Additional delay modules are employed to coordinate the computation speed of each module with the cycle time of PM.



Figure 1: *Simulation of a NOR-gate with pools of noisy spiking neurons*

The module for a NOR-gate (see Figure 1) consists of 3 pools A, B, C of neurons that are excitatory (inhibitory) if the arrow that begins at that pool has the label E (respectively I). An arrow indicates that there is a synapse from each neuron in the preceding pool to each neuron in the subsequent pool.

The weights on synapses from pools A and B into pool C are chosen so large, that already when one of A, B represents a "1", the induced negative potential in C is so strong that it cancels out the largest possible "peak" of the next positive potential wave of length $\leq R/2$ that is induced by PM in neurons from C. One can employ auxiliary delay mechanisms (not shown) to make sure that the induced negative potential in C lasts sufficiently long to achieve this in spite of small random fluctuations in the cycle time of PM. Thus the firing activity in C during the initial period of length $R/3$ of the next potential wave from PM represents a "1" if and only if both A and B have received input "0".

We employ *"self-excitatory pools"* in order to store bits that encode the current state of the simulated automaton D, as well as input- and output-bits. These are pools of excitatory neurons that are interconnected by a complete graph, and whose parameters are chosen in such a way that a positive potential (such as that induced by PM) can "kick it off" so that it moves to a state of continuous self-excited firing (representing a "1"), until its activity is halted by a sufficiently long negative potential wave that is induced by some pool of inhibitory neurons. ∎

It is shown in the proof of Theorem 1 that any boolean circuit consisting of NOR-gates can be simulated. This implies:

Corollary 2: *Any boolean function can be computed by a sufficiently large network of noisy spiking neurons (that satisfy our weak assumptions) with arbitrarily high probability of correctness.*

3 Fast Simulation of Threshold Circuits via Shunting Inhibition

For biologically realistic parameters, each computation step in the previously constructed network takes around 25 msec (see point c) in section 4). However it is well-known that biological neural systems can carry out complex computations within just 100 msec (Churchland, Sejnowski, 1992). A closer inspection of the preceding construction shows, that one can simulate with the same speed also OR- and NOR-gates with a much larger fan-in than just 2. However wellknown results from theoretical computer science (see the results about the complexity class AC^O in the survey article by Johnson in (van Leeuwen, 1990)) imply that for *any fixed* number of layers the computational power of circuits with gates for OR, NOR, AND, NOT remains very weak, even if one allows *any* polynomial size fan-in for such gates.

In contrast to that, the construction in this section will show that by using a biologically more realistic model for a noisy spiking neuron, one can in principle simulate within 100 msec 3 or more layers of a boolean circuit that employs substantially more powerful boolean gates: *threshold gates* (i.e. "Mc Culloch-Pitts neurons", also called "perceptrons"). The use of these gates provides a giant leap in computational power for boolean circuits with a small number of layers: Whereas besides ADDITION almost no interesting boolean function can be computed

by the former type of circuit with *any* fixed number of layers, polynomial size circuits of *threshold gates* (i.e. *threshold circuits*) with just 3 layers (and weights $\in \{-1, 1, 0\}$) are known to be able to MULTIPLY, DIVIDE and SORT binary numbers of *arbitrary* bit length. In fact, in spite of many years of intensive research, one has not been able to exhibit a *single concrete computational problem in the complexity classes P or NP* that can be shown to be *not* computable by a polynomial size threshold circuit with 3 layers (for threshold circuits with integer weights of *unbounded* size the same holds already for just 2 layers).

In the neuron model that we have discussed so far in this article, we have assumed (as it is common in the spike response model) that the potential $P_v(t)$ at the trigger zone of neuron v depends *linearly* on all the terms $w_{u,v} \cdot \varepsilon_{u,v}(t-s)$. There exists however ample biological evidence that this assumption is not appropriate for certain types of synapses. An example are synapses that carry out *shunting inhibition* (see. e.g. (Abeles, 1991) and (Shepherd, 1990)). When a synapse of this type (located on the dendritic tree of a neuron v) is activated, it basically erases (through a short circuit mechanism) for a short time all EPSP's that pass the location of this synapse on their way to the trigger zone of v. However in contrast to those IPSP's that occur linearly in the formula for $P_v(t)$, the activation of such synapse for *shunting* inhibition has *no impact* on those EPSP's that travel to the trigger zone of v through another part of its dendritic tree. We model shunting inhibition in our framework as follows. We write Γ for the subset of all neurons γ in V that can "veto" other synapses $\langle u, v\rangle$ via shunting inhibition (we assume that the neurons in Γ have no other role apart from that). We allow in our formal model that certain γ in Γ are assigned as *label* to certain synapses $\langle u, v\rangle$ that have an *excitatory* response function $\varepsilon_{u,v}$. If γ is a label of $\langle u, v\rangle$, then this models the situation that γ can intercept EPSP's from u on their way to the trigger zone of v via shunting inhibition. We then define

$$P_v(t) = \sum_{u \in V \,:\, \langle u,v\rangle \in E} \left(\sum_{s \in F_u \,:\, s < t} w_{u,v} \cdot \varepsilon_{u,v}(t-s) \cdot \prod_{\gamma \text{ is label of } \langle u,v\rangle} S_\gamma(t) \right) ,$$

where we assume that $S_\gamma(t) \in [0, 1]$ is arbitrarily close to 0 for a short time interval after neuron γ has fired, and else equal to 1. The firing mechanism for neurons $\gamma \in \Gamma$ is defined like for all other neurons.

Theorem 3: *One can simulate any threshold circuit T by a sufficiently large network $N(T)$ of noisy spiking neurons with shunting inhibition (with arbitrarily high probability of correctness). The computation time of $N(T)$ does not depend on the number of gates in each layer, and is proportional to the number of layers in the threshold circuit T.*

Idea of the ***proof*** *of Theorem 3:* We had already discussed in our sketch of the proof of Theorem 1 the difficulty to simulate an AND-gate with *weak coding* of bits. The same difficulties arise in an even more drastic way if one wants to simulate a threshold gate with large fan-in.

The left part of Figure 2 indicates that with the help of shunting inhibition one can transform via an intermediate pool of neurons $B_1 \subseteq \Gamma$ the bit that is weakly encoded by A_1 into a contribution to $P_v(t)$ for neurons $v \in C$ that is throughout a time interval J arbitrarily close to 0 if A_1 encodes a "0", and *arbitrarily close to some constant* $P^* > 0$ if A_1 encodes a "1" (we will call this a "*strong coding*" of a bit). Obviously it is rather easy to realize a threshold gate if one can make use of such *strong coding* of bits.

Without shunting inhibition one could work with strong coding of bits only under the biologically less plausible assumption of a pool H that can be switched "on" and "off", and which sends to other neurons immediately after it is switched "on" a positive potential with an almost constant value P^*, that does *not* depend on the precise height and length of the potential wave that has switched H "on". We do *not* assume the existence of such pools H in our model.



Figure 2: *Realization of a threshold gate G via shunting inhibition (SI).*

The task of the module in Figure 2 is to simulate with noisy spiking neurons a given boolean threshold gate G that outputs 1 if $\sum_{i=1}^{n} \alpha_i x_i \geq \Theta$, and 0 else. For simplicity Figure 2 shows only the pool A_1 whose firing activity encodes (in weak coding) the first input bit x_1. The other input bits are represented (in weak coding) simultaneously in pools $A_2, \ldots, A_n$ parallel to A_1. If $x_1 = 0$, then the firing activity in pool A_1 is low, hence the shunting inhibition from pool B_1 intercepts those EPSP's that are sent from BN^+ to each neuron v in pool C. More precisely, we assume that each pool B_i associated with a different input bit x_i carries out shunting inhibition on a *different* subtree of the dendritic tree of such neuron v (where each such subtree receives EPSP's from BN^+). If $x_1 = 1$, the higher firing activity in pool A_1 inhibits the neurons in B_1 for some time period. Hence during the relevant time interval BN^+ contributes an almost constant positive summand to the potential $P_v(t)$ of neurons v in C. By choosing w_v^+ and w_v^- appropriately, one can achieve that during this time interval the potential $P_v(t)$ of neurons v in C is arbitrarily much positive if $\sum_{i=1}^{n} \alpha_i x_i \geq \Theta$, and arbitrarily much negative if $\sum_{i=1}^{n} \alpha_i x_i < \Theta$. Hence the activity level of C encodes the output bit of the threshold gate G (in *weak* coding). The purpose of the subsequent pools D and F is to synchronize (with the help of "double-negation") the output of this module via PM. In this way one can achieve that all input "bits" to another module that simulates a threshold gate on the next layer of circuit T arrive simultaneously. ∎

4 Conclusion

The described networks were constructed in such a way that they allow us to *prove* (on the basis of our *weak* assumptions) that they carry out the desired simulation with arbitrarily high probability of correctness. Several aspects of these constructions can be made simpler and/or biologically more plausible, at the price of making the proofs even more complicated and/or

requiring more concrete assumptions about the spiking neurons. For example all complete bipartite graphs between pools of neurons can be replaced by random graphs of a sufficiently high density, and one could employ short bursts of firings instead of single spikes, as well as feedback-loops.

Nevertheless our constructions throw new light on various experimental data, and on our attempts to understand neural computation and coding:

a) The spike trains which result from computations in the here constructed networks encode information in a way that presents an interesting *compromise* between *single-spike coding* and *ensemble coding*, combining the computation-speed of the former with the noise robustness of the latter.

b) If one would record all firing times of a few arbitrarily chosen neurons in our networks during many repetitions of the same computation, one is likely to see that each run yields quite different seemingly random firing sequences, where however a few firing patterns will occur more frequently than could be explained by mere chance. This is consistent with the experimental results reported in (Abeles, 1991), and one should also note that the *synfire chains* of (Abeles, 1991) have many features in common with the here constructed networks.

c) If one plugs in biologically realistic values (see (Shepherd, 1990), (Churchland, Sejnowski, 1992)) for the length of transmission delays (around 5 msec) and the duration of EPSP's and IPSP's (around 15 msec for fast PSP's), then the timing of computation steps in the here constructed networks happens to be biologically plausible: The computation time of our modules for NOR- and threshold gates comes out to be not more than 25 msec. The cycle time of PM is according to our construction a bit larger than the duration of a single EPSP respectively IPSP, and hence in the same range. The resulting oscillation frequency of PM (around 40 Hz) is a plausible value for the clock-speed of computations in biological neural systems, since it is in the same range as for example the fast oscillations that appear in the EEG of a mentally active person. We also would like to point out that all our constructions work just as well with a synfire chain instead of the oscillator PM. The use of synfire chains instead of an oscillator PM may be viewed by some as biologically more realistic, since the single neuron recordings by Abeles did not provide any evidence for the existence of oscillators in higher areas of the cortex.

d) Our constructions provide new hypotheses about the computational roles of regular and shunting *inhibition*, that go far beyond their usually assumed roles.

e) We provide new hypotheses regarding the computational role of randomly firing neurons, and of EPSP's and IPSP's that arrive through synapses at distal parts of biological neurons (see the use of BN^+ and BN^- in our constructions).

f) The experimentally observed fact that only many EPSP's together can trigger the firing of (most) biological neurons, receives a completely natural explanation in the context of our computations with noisy spiking neurons: since the arrival of just one or two EPSP's contains little information, a neuron that would fire as a result of very few EPSP's would mainly amplify the "noise", and contribute little to the processing of *information*.

g) The constructions of this article provide a missing link between the high-level model for brain-like architectures in (Valiant, 1994), and realistic models for biological neurons. Valiant's framework for the investigation of computing and learning in brain-like architectures employs

"neuroids" as atomic units, where each neuroid combines features of a DFA with those of a threshold gate. The results of this article show that such neuroids can in fact be realized by suitable systems of noisy spiking neurons.

References:

M. Abeles. (1991) Corticonics: Neural Circuits of the Cerebral Cortex. *Cambridge University Press.*

N. Alon, J. H. Spencer, P. Erdos. (1992) The Probabilitistic Method. *Wiley.*

P. S. Churchland, T. J. Sejnowski. (1992) The Computational Brain. *MIT-Press.*

W. Gerstner, J. L. van Hemmen. (1994) How to describe neuronal activity: spikes, rates, or assemblies? *Advances in Neural Information Processing Systems, vol. 6, Morgan Kaufmann*: 463-470.

W. Maass. (1995a) On the computational complexity of networks of spiking neurons (extended abstract). *Advances in Neural Information Processing Systems, vol. 7 (Proceedings of NIPS '94), MIT-Press*, 183-190.

W. Maass. (1995b) Lower bounds for the computational power of networks of spiking neurons. *Neural Computation* 8:1, to appear.

W. Maass. (1995c) Fast analog computations with noisy spiking neurons. In preparation.

G. M. Shepherd. (1990) The Synaptic Organization of the Brain. *Oxford University Press.*

L. G. Valiant. (1994) Circuits of the Mind. *Oxford University Press.*

J. van Leeuwen, ed. (1990) Handbook of Theoretical Computer Science, vol. A: Algorithms and Complexity. *MIT-Press.*